


Automatic Card Collector with RFID Reader Automatic Card Reclaimer with RFID Reader

Model No.: F2-RFID



FEATURES:

- --With ISO14443A/B RFID card reader integrated support typical card: Mifare S50,S70 etc...
- --Industry conceiving, surface dealing with roast paint, well bearable cubing and rotting. Be suitable to all kinds of bad environment, such as high, low ,and mush dust, etc.
- --Passage ways of receiving card. Be good suitable to all kinds of distortion card.
- --Rational construction, the speed of receiving card is very fast
- --Obligate many card screens, receiving and flipping card can control by your requirement.
- --Smart protect function of card machine.
- --24VDC/1.5A
- --RS-232

APPLICATIONS:


- (1)Parking issuing system
- (2) Vending Machine
- (3) Automatic ticketing machines



Technology Parameters


	T	
Power Supply	24VDC(Max. current 1.5A, MIN current 0.1A)	
Operating temperature	-20 to 60 C-degrees	
Operating humidity	30-90% RH	
Interface	RS232	
Payout position	many card screens controlling	
Using condition	use in the installing case	
Card size	54 +/- 1.5mm cards relief	
	85 +/- 1.5mm long card	
	0.2-2.0mm thick card(adjustable)	
Cards or paper cards	ICO144424/D 12 ECMIL- DEID Delegation Coul-	
material	ISO14443A/B 13.56MHz RFID Polyester Cards	
Receiving card time	about 0.3/sec at quickest	
Weight	650g	
Dimension	127*94*83mm	

CONNECTIONS:



www.lintechtt.com





Power Connection:

<u>No.</u>	<u>Detail</u>	Applications
1	+ 24VDC	+24VDC Power Input
2	GND	Ground
3	GND	Ground
4	BPS	+24VDC BackUp Power Input

RS-232 Connection:

<u>No.</u>	<u>Detail</u>	Applications
1	RXD	PC Receive Signal
2	TXD	PC Sent Signal
3	SGN	Ground



DIMENSIONS:

